



## INSTALLATION INSTRUCTIONS

Installation is simple with The Leaf Terminator™, the only COMMERCIAL gutter protection system available today.

1. The Leaf Terminator™ has been manufactured for any easy, one person installation. Before you begin, make sure all gutters, downspouts, and underground lines are clean, running freely and angled properly. The type of roof will determine how The Leaf Terminator™ will be installed. Either a fascia mount or under the 1<sup>st</sup> or 2<sup>nd</sup> shingle.
2. The Leaf Terminator™ will work on gutters ranging from 5" to 15", including box gutters and roof pitches from flat to 15/12. The Leaf Terminator™ comes in 5' sections and has a 1" built-in overlap so you can easily connect to your next piece of The Leaf Terminator™. The Leaf Terminator™ mounts easily onto the front of the gutter.
3. A. To install The Leaf Terminator™ **under the shingle**, take a 12" drywall knife and slide it under the second row shingle to loosen the tar seal. Once you have loosened the seal, determine the angle of the bend that you will need to install The Leaf Terminator™. (On a 4/12 or 5/12 pitch roof a bend is not required.) All other roof pitches require a metal brake bend if you chose to install The Leaf Terminator™ under the shingles.  
  
B. To install The Leaf Terminator™ **on the fascia**, measure the width of the gutter from the lip to the back. For instance, if it is a 6" gutter, you measure 6" from the nose of The Leaf Terminator™ and mark. From the 6" mark, you measure back 3/4". Your total measurement should be 6 3/4". Cut The Leaf Terminator™ at the 6 3/4" mark, depending on how much clearance there is from the back of the gutter to the roof edge. Bend The Leaf Terminator™ up at a 90 degree angle. Once this is complete, screw into the fascia through the 90 degree angle, then screw to the lip of the gutter.
4. We suggest putting a zip screw every 12 inches.